

PCT/EP2004/005134  
Weckerle GmbH

October 19, 2005  
W100681WO JH/Hdt/pes

**DEVICE AND METHOD FOR PRODUCING OBJECTS MOLDED FROM PASTE-LIKE  
MATERIALS, AND PRODUCTION MOLD**

5

The invention relates to a device for producing objects that are molded from paste-like materials as, for example, lipsticks.

Such a device is, for example, shown in FR 2 729 278. According to this docu-  
10 ment, silicone molds are provided which are freely suspended top down in a sup-  
port of a filling device. The material is filled in hot, and hardens in the mold. Af-  
ter hardening, a small basket is applied from top, this means at the lipstick's rear  
end, and a vacuum is applied on the outer surface of the silicone mold, whereby it  
expands and releases the lipstick body formed in its interior. Subsequently, the  
15 lipstick can be removed towards the top by means of the small basket. A problem  
of this method is that the silicone mold loses its dimensional stability, in particu-  
lar if used longer, since, among others the mold is deformed with every produc-  
tion process for removing the lipstick. On the other hand, this very deformation  
offers the possibility of removing the hardened lipstick from the mold with little  
20 effort.

Therefore, it is the problem of the invention to provide a device for producing  
objects made of paste-like materials, which – on the one hand – ensures the high  
dimensional stability of the product, and – on the other hand – ensures the object's  
25 easy removability from the mold after hardening.

This problem is solved by a device with the features of claim 1, a production mold  
according to claim 13, and a method according to claim 15. Advantageous further

## Translation of the officially amended description

- 2 -

developments of the invention are the subject matter of the respective dependent claims.

According to the invention, a mold is provided in which an elastic mold part, for  
5 example made of silicone, is used not freely suspended, but the mold part is arranged in a dimensionally stable housing element, ensuring that the mold part is not deformed at least during the filling process. To this end, the housing element has a housing space, in which the mold part abuts on housing element's inner walls either directly or with interposition of a thin fluid layer. This ensures that  
10 the mold part does not alter when the paste-like material is filled in, but maintains its original shape (in unfilled state). This causes that during the production of objects, for example lipsticks, made of paste-like materials by far lesser production tolerances occur than this is the case with known methods. It is not required that the mold part abuts on the housing element with its entire surface, but that those  
15 surfaces, which are decisive for the object's dimensional stability, abut on the housing element, such as, for example, the coat portion of a lipstick.

Discharge of the mold is done in that a movable part of the housing element is made movable such that the housing space for housing the mold part is enlarged  
20 when the movable part is moved. Thus, the walls of the mold part are stretched in a defined manner, and thereby are moved away from the hardened paste-like material. The hardened object can now be removed from the mold part – in the case of lipstick production, for example by means of a plugged-on small basket. The advantage generated by the movable part of the housing element is that the housing  
25 space is only enlarged by a defined value, which also entails a only defined deformation of the mold part. During removal, the mold part is thus not stretched in an undefined manner and possibly overstretched, which would result in a decrease of the dimensional stability of the mold part. Instead of or in addition to the movement of the movable part, a thin fluid layer, such as for example ~~air or~~ water,  
30 respectively an oil layer, may be provided between the mold part and the housing

## Translation of the officially amended description

- 3 -

element. A defined slight enlargement of the mold part can then be achieved if the fluid is removed from this gap, for example by moving the movable part. The mold part is herein slightly expanded by a small defined value, which enables the formed object's removal from the mold part, but on the other hand prevents an  
5 overstretching of the mold part during removal. All kinds of ~~gaseous~~, liquid or viscous, yet flowable materials can be used as fluid. It is essential that the existing fluid volume is closed so that a vacuum acts upon the walls of the mold part if the movable part is moved away from the mold part. Naturally, it is likewise possible to enlarge the housing space via the movable part and only thereafter to stretch the  
10 mold part by application of a vacuum.

Preferably, the external wall of the mold part is made in the shape of a cone, whereas the corresponding moveable part of the housing element is made in the shape of a cone-shaped recess, which is axially movable away from the mold part.  
15 The vacuum caused thereby causes that the mold part is slightly stretched. Since preferably a block element is provided for the movement of the movable part, the maximum degree of deformation of the mold part is defined for the removal of the hardened object; in the case of adjustable block elements, it even is adjustable. The block element can be adjusted such that the best compromise between easy  
20 removal and little stretching of the mold part is achieved.

Preferably, the housing element for the mold part is made of metal and, together with it, forms a mold which can be inserted like a common conventional lipstick mold in a conventional production machine, such as a revolving-cycle lipstick  
25 pouring-machine. To this end, the housing element preferably comprises in its upper and external range standardized adapter surfaces, for example in the shape of flanges or cantilevers.

Preferably, the elastic mold is made of silicone. However, it can also be made of  
30 arbitrary other elastic materials such as different kinds of rubber and plastic,

## Translation of the officially amended description

- 4 -

which have a high elasticity with a reversible stretching over 10%, preferably over 30%, and which are chemically insensitive against the objects to be produced.

In the following, the invention is described in the schematic drawing by way of an  
5 example.

Figs. 1a and b show a lateral view of a mold with inserted mold for producing a lipstick in two lateral views, at 90° offset,

10 Fig. 2 shows a perspective view of the mold of fig. 1 diagonally from above, and

Fig. 3 shows an enlarged section of the mold of fig. 1 in longitudinal section.

15

The figures show a mold 10, which can, for example, be used in a stationary or moving support of a lipstick filling machine. Such a lipstick filling machine (not shown), which is, for example, represented by revolving-cycle machines, comprises a filling device, filling a warm liquid paste-like material into a mold, the  
20 paste-like material hardens in the mold, and a removing device removes the thus formed lipstick by means of a small basket, pressed onto the hardened material from the top, which is generally the small support basket used in the lipstick. When the lipstick is removed by the small basket, the mold part is slightly expanded, so that the formed lipstick is easily released.

25

Such a mold is the mold 10, which is shown in figs. 1 to 3. Mold 10 comprises an external, sheath-like stabile housing element 12, which has a filling aperture at its upper end 14. The upper end has a cantilever 16 protruding to the outside, for inserting the mold 10 into the support of a lipstick filling machine. The stabile mold  
30 part consists of metal, in particular aluminum or other light-metal alloys, and has

## Translation of the officially amended description

- 5 -

a bottom part 18, from which a centering thorn 20 extends vertically upwards. An axially movable release element 22 is supported on this thorn, which is pressed into a first illustrated filling position by means of a spring 24, supported against the bottom part 18 of the mold part 12. In said filling position, an inner cone 26, which is arranged at the upper end of the movable release element 22, abuts the external wall of an elastic mold part 28 in a planar fashion, said elastic mold part preferably consisting of silicone, into the interior space 30 of which the paste-like material is introduced for forming the lipstick. The mold part 28 is fixed in an inner groove 34 of the housing element 12 by means of a cantilever 32. To move the movable release element 22, 26 downwards against the force of the spring 24, an actuating stud 36 is provided, running transversely to the axis, which can be actuated downwards into a release position of the upper cone by an actuation organ (not shown) of a lipstick filling machine, by means of which the elastic mold part 28 is stretched due to the low pressure generated when the inner cone is moved downwards, which in turn allows to remove the hardened lipstick material in the mold part 28 from the mold 10 by means of a small basket upwardly through the aperture 14. To ensure a smooth function, the external wall of the elastic mold part 28 does not have to completely abut on the inner cone 26. It is also possible to arrange a thin fluid layer, for example ~~an air layer or~~ a liquid layer, such as water or oil layer, between the inner cone 26 and the external wall of the mold part 28; when the actuation stud 36 is actuated downwards, the thin fluid layer causes that the elastic mold part is correspondingly stretched due to the occurrence of the vacuum when the inner cone 26 is pulled down. This in turn causes the release of the lipstick formed in the inner space 30 of the mold part 28. Of course, a low pressure can also be applied to the gap between the mold part 28 and the housing element 12 by actuating the release element into the release position.

To fill the mold part 18, a filling piece 40, in particular made of metal, is provided, which can be plugged onto the upper end 14 of the housing element 12.

The filling piece 40 is formed as a hollow cylinder, the inner wall 50 of which has at the lower end of the filling piece 40 exactly the same diameter as the inner diameter 52 of the cylindrical part of the mold part 18. In an upper section 58, the inner diameter is slightly expanded in a funnel-like manner. From bottom to top, the mold part has at its external circumference two superimposed cone-shaped circumferential surfaces 42, 44. An orbital shoulder 54 is formed at the upper edge of the upper cone-shaped circumferential surface 44.

This filling piece 40 is pressed or plugged onto the housing element prior to filling, until its shoulder 54 abuts on the upper side 56 of the housing element 12. Then, the external circumferential surfaces 42, 44 abut on a corresponding inner cone 46 of the mold part 18 and on a corresponding inner cone 48 of the housing element 12, and thus securely seal the upper portion of the mold 10 between the housing element 12 and the mold part 18. At this, the inner wall 50 of the filling piece 40 is in alignment with the inner diameter 52 of the mold part 18. The mold 10 is filled until the material slightly projects into the filling piece 40. After hardening of the material, the filling piece 40 is now pulled off towards the top, which is eased since the inner wall 50 is slightly cone-shaped extended in the lower direction. Then, the small basket for removal of the object is pressed onto the material pin protruding upwardly from the mold part. Due to the fact that the circumference of the material portion for housing the small basket is defined by the exactly defined inner diameter of the inner wall 50 of the filling piece 40, the elastic mold part does not introduce any tolerances into production.

Of course, the actuation of the actuation stud 36 does not have to be centrally controlled by the lipstick machine, but can be coupled mechanically by the removing device alone, for example in coordination with plugging the small basket onto the hardened lipstick material.

## **Translation of the officially amended description**

- 7 -

The dimensionally stable part of the housing element, in particular the inner cone 26 consists of any dimensionally stable material, such as metal, ceramic, or plastic, whereas the elastic mold part can consist of any kind of a rubber-elastic material with an elastic expansibility of at least 10%, in particular silicone, latex, or  
5 other highly-elastic polymers.

The housing space of the housing element for the mold part is preferably provided in the inner space of the housing element. Like in the drawings, the housing element may be made as rotation-cylindrical body, in which, for example, the movable part is axially movable. However, bodies with different shapes, for example  
10 with quadratic or polygonal base surface are also conceivable.

Of course, a thin fluid layer may also be arranged in the relaxed state between the mold part 18 and the cone surface, respectively inner cone 26, which can opti-  
15 mally stabilize the silicone mold (mold part 18).

PCT/EP2004/005134  
Weckerle GmbH

October 19, 2005  
W100681WO JH/Hdt/pes

**Claims**

1. Device for producing objects, for example lipsticks, that are molded from  
5 paste-like materials, while using an elastic mold part (28), into which the  
paste-like material is introduced by means of a filling device, is hardened,  
and from which the at least largely hardened object is removed by a re-  
moving device while said mold part is elastically stretched,  
characterized in that a dimensionally stable housing element (12) is pro-  
10 vided for housing said mold part, wherein said housing element is held in-  
side a stationary or moveable support of said device,  
- wherein said mold part (28) is placed in a housing space of said  
housing element at least during the filling and removal process, and  
- wherein said housing space can be enlarged by moving a moveable,  
15 dimensionally stable part (26) of the housing element (12) for removing  
the object.
2. Device according to claim 1, characterized in that during the filling proc-  
ess a thin fluid layer is placed between said mold part and said housing  
20 element, which is removable from said housing element for the removal  
process.
3. Device according to claims 1 or 2, characterized in that said fluid layer has  
a thickness of at most 5 mm, preferably at most 2 mm.
- 25 4. Device according to any of the preceding claims, characterized in that a  
coat portion of said mold part (28) at least predominantly, preferably com-  
pletely abuts in a planar fashion on said housing element (12).



## Translation of the officially amended claims

- 2 -

5. Device according to any of the preceding claims, characterized in that said housing element (12) comprises a release element (22, 26) which is movable in relation to said mold in a planar fashion (28).
- 5 6. Device according to claim 5,  
characterized in that the path of said movable release element (22, 26) is in its end positions limited by block elements.
7. Device according to claims 5 or 6,  
10 characterized in that between said mold part (28) and said movable release element (26) a closed gas, respectively fluid volume is arranged to form a thin fluid layer.
8. Device according to any of claims 5 to 7,  
15 characterized in that an actuation element is provided which, controlled by a control element of said device or by a removing device, actuates the movable part of said housing element during the removal process and/or sucks said fluid off the gap between said mold part (28) and said housing element (12).
- 20 9. Device according to any of the preceding claims,  
characterized in that the side of said mold part (28) which faces said housing element (26) has the shape of a cone, and that said housing element (26) is formed as complementary cone-shaped recess (inner cone).
- 25 10. Device according to any of the preceding claims,  
characterized in that said housing element (12) is made of metal, in particular of aluminum.
- 30 11. Device according to any of the preceding claims,  
characterized in that said mold part (28) is made of silicone.

## Translation of the officially amended claims

- 3 -

12. Device according to any of the preceding claims,  
characterized in that said mold part (28) comprises a flange (32) at its up-  
per filling end, which is fixed in said housing element (12).
- 5
13. Device according to any of the preceding claims,  
characterized in that said housing element (12) comprises a standardized  
adapter (16) to be housed in a traditional revolving-cycle lipstick pouring  
machine.
- 10
14. Production mold (10) for producing objects, for example lipsticks, that are  
molded from paste-like materials, in particular for a device according to  
any of the preceding claims, comprising
- an elastic mold part (28) for housing the paste-like material,
  - 15 - a dimensionally stable housing element (12) for housing the elastic  
mold part (28), wherein said housing element is formed to be housed in-  
side a stationary or moveable support of a production machine for objects  
made of paste-like materials,
  - wherein said mold part (28) is placed in a housing space of said
  - 20 housing element (12), and
  - wherein said housing space can be enlarged by moving a moveable,  
dimensionally stable part (26) of the housing element (12) for removing  
the object.
- 25
15. Production mold according to claim 1, wherein during the filling process a  
thin fluid layer is placed between said mold part (28) and said housing ele-  
ment (26), which is removable from the gap between said mold part and  
said housing element for the removal process.
- 30
16. Production mold according to claims 14 or 15, wherein a dimensionally  
stable, hollow-cylindrical filling element (40), for example made of metal,

is provided, which can be placed onto said housing element (12), respectively onto said mold part (18), and the inner wall (50) of which forms the mold for an end section of said object.

5     17.     Method for producing objects, for example lipsticks, that are molded from paste-like materials, while using an elastic mold part (28), into which the paste-like material is introduced, hardened, and from which the at least largely hardened object is removed while said mold part is elastically stretched,

10     characterized in that

-         said mold part (28) is placed in a housing space of a dimensionally stable housing element (12) during the filling and removal process in order to prevent/limit the stretching of said mold part, and that for stretching said mold part for the removal process said housing space is enlarged by moving a moveable, dimensionally stable part (26) of the housing element (12).

18.     Method according to claim 17, wherein during the filling process a thin fluid layer is provided between said mold part and said housing element, having a maximum thickness of 5 mm, preferably of maximally 2 mm, said fluid layer is removed from the gap for the removal process in order to generate a vacuum acting upon the external wall of said mold part.

19.     Method according to claims 17 or 18, wherein said mold part (28) at least predominantly abuts the housing element (26) during the filling process.

20. Device for producing objects, for example lipsticks, that are molded from paste-like materials, while using an elastic mold part (28), into which the paste-like material is introduced by means of a filling device, is hardened, and from which the at least largely hardened object is removed by a removing device while said mold part is elastically stretched, characterized in that a dimensionally stable housing element (12) is provided for housing said mold part, wherein said housing element is held inside a stationary or moveable support of said device,
- 5
- 10 - wherein said mold part (28) is placed in a housing space of said housing element at least during the filling and removal process, and
- wherein during the filling process a thin fluid layer is placed between said mold part and said housing element, which is removable from said housing element for the removal process.
- 15
21. Device according to claim 20, characterized in that said fluid layer has a thickness of at most 5 mm, preferably at most 2 mm.
22. Device according to any of claims 20 or 21, characterized in that between said mold part (28) and said movable release element (26) a closed gas, respectively fluid volume is arranged to form a thin fluid layer.
- 20
23. Device according to any of claims 20 to 22, characterized in that an actuation element is provided which, controlled by a control element of said device or by a removing device, sucks said fluid off the gap between said mold part (28) and said housing element (12).
- 25
24. Device according to any of the preceding claims,

## Translation of the officially amended claims

- 6 -

characterized in that the side of said mold part (28) which faces said housing element (26) has the shape of a cone, and that said housing element (26) is formed as complementary cone-shaped recess (inner cone).

- 5     25.     Device according to any of the preceding claims,  
         characterized in that said housing element (12) is made of metal, in particular of aluminum.
26.     Device according to any of the preceding claims,  
10       characterized in that said mold part (28) is made of silicone.
27.     Device according to any of the preceding claims,  
         characterized in that said mold part (28) comprises a flange (32) at its upper filling end, which is fixed in said housing element (12).
- 15       28.     Device according to any of the preceding claims,  
         characterized in that said housing element (12) comprises a standardized adapter (16) to be housed in a traditional revolving-cycle lipstick pouring machine.
- 20       29.     Production mold (10) for producing objects, for example lipsticks, that are molded from paste-like materials, in particular for a device according to any of the preceding claims, comprising
- an elastic mold part (28) for housing the paste-like material,
  - 25       -       a dimensionally stable housing element (12) for housing the elastic mold part (28), wherein said housing element is formed to be housed inside a stationary or moveable support of a production machine for objects made of paste-like materials,
  - wherein said mold part (28) is placed in a housing space of said  
30       housing element (12), and

## Translation of the officially amended claims

- 7 -

- wherein during the filling process a thin fluid layer is placed between said mold part (28) and said housing element (26), which is removable from the gap between said mold part and said housing element for the removal process.

5

30. Production mold according to claim 29, wherein a dimensionally stable, hollow-cylindrical filling element (40), for example made of metal, is provided, which can be placed onto said housing element (12), respectively onto said mold part (18), and the inner wall (50) of which forms the mold for an end section of said object.

10

31. Method for producing objects, for example lipsticks, that are molded from paste-like materials, while using an elastic mold part (28), into which the paste-like material is introduced, hardened, and from which the at least largely hardened object is removed while said mold part is elastically stretched,  
characterized in that

15

- said mold part (28) is placed in a housing space of a dimensionally stable housing element (12) during the filling and removal process in order to prevent/limit the stretching of said mold part, and that during the filling process a thin fluid layer is provided between said mold part and said housing element, having a maximum thickness of 5 mm, preferably of maximally 2 mm, said fluid layer is removed from the gap for the removal process in order to generate a vacuum acting upon the external wall of said mold part.

20

25